

MARKET INSIGHTS 01 / TEASER

BESS Market

Germany. Europe. Worldwide.

Value creation, technology and economics
for viable storage projects.

UTILITY

CO-LOCATION

HYBRID C&I

Mario Willatowski

Dipl.-Ing. | Executive MBA | Six Sigma Black Belt

OCTOBER 2026

Design v2 | 19.10.2026 - Content updated 12.10.2026

BESS Market Germany · EU · Worldwide

Growing demand for storage. What makes a viable project?

Grid congestion, wind and PV, electrification and security of supply increase the need for flexibility. Economic value depends on suitable grid access, technology and a robust operating and revenue model.

MARKET DRIVER	SYSTEM NEED	BESS APPLICATION
Congestion & slow grid expansion	→ Connection power limited at certain times	→ Co-location · local congestion relief
More wind and photovoltaics	→ Generation and demand at different times	→ Energy shifting · less curtailment
Flexibility & system stability	→ Fast response and controllability required	→ Reserves · grid-support functions
Energy costs & price volatility	→ Spreads, demand peaks and expensive imports	→ Trading · peak shaving · self-consumption
Electrification & new loads	→ Charging hubs, heat and data centres	→ Load management · connection utilisation
Geopolitics & security of supply	→ Import dependence and disruption risks	→ Hybrid systems · resilience · diversification

REEEM illustration based on IEA Electricity 2026 (Grids, Flexibility) and Global Critical Minerals Outlook 2025. Sources and limitations in the full report.

What the publication brings together

Value chains and project development · Germany, EU and international markets · Grids and technology · Revenue stacks · CAPEX, OPEX, TCO and financing.

[Request the full publication →](#)

Enter your contact details on the download page. After personal review and approval, you receive the PDF by email as an attachment and with a time-limited download link.

[Executive Summary and contents → page 2](#)

Executive Summary

Market drivers: Grid congestion, slow grid expansion, wind and PV, and electrification increase flexibility needs. Energy costs and geopolitics affect demand and supply chains. Location determines which benefits can be realised.

Growth: Germany, the EU and global markets use different forecast bases. Distinguish CAGR, installed capacity and annual additions; a large connection pipeline is not yet a built market.

Technology and revenues: Utility BESS, PV/wind co-location and hybrid C&I; systems need distinct operating models. Grid access, usable energy, efficiency and availability constrain the revenue stack. The same flexibility cannot be sold twice.

Investment: CAPEX alone is insufficient. Include OPEX, charging energy, losses, augmentation and decommissioning in TCO and LCOS. Bankability depends on robust rights, warranties, counterparties and revenue scenarios.

Outline / contents of the full report

73 pages · Page references relate to the full publication, not to this teaser.


Chapters	Topic	Pages
1-2	Executive Summary · Growth, forecasts and CAGR	2-4
3-7	Value chains · Raw materials · Supply chains · Project timelines and roles	5-10
8-11	Grids · Voltage levels · Maturity assessment · Grid connection	11-14
12-18	Germany, Europe and global markets · Country profiles · Revenue stacks and optimisation	15-28
19-25	Technology · BMS, EMS, SCADA · Single-line diagrams · Fraunhofer, TRL and trends	29-42
26-29	Regulation · Standards · Cybersecurity · VPPs and e-mobility	43-48
30-33	CAPEX, OPEX, TCO and LCOS · PV/wind co-location · Financing and risks	49-57
34-36	Original-analysis review · Methodology · Sources and author	58-73

Condensed summary of the full report. Source base: IEA, Fraunhofer, Aurora/Agora, SolarPower Europe, grid operators and regulators. Dated evidence and model limitations are provided in the respective chapters.

[Request the full publication with all sources →](#)

Design technology and economics together

An example puts the scale in perspective



Illustrative REEEM model: 50 MW / 100 MWh, EUR 25 million CAPEX and EUR 0.75 million annual OPEX excluding charging energy. Own assumptions, not a market average or supplier offer.

Co-location with PV or wind

Shared connections, roads and infrastructure can reduce costs. Additional integration, connection limits and charging-energy value also belong in the calculation. The full report compares euros and percentages and explains the model limitations.

For developers, IPPs, EPCs, operators and investors

The publication connects market opportunities, technical design and investment decisions, including EMS, BMS, SCADA, cybersecurity and supply chains.

[Request the full publication →](#)

[Analysis, services and mandates → Expertise](#)

Mario Willatowski · Dipl.-Ing. Electrical Engineering · Executive MBA
REEEM Consulting & Partner

Sources: IEA Electricity 2026; IEA Critical Minerals 2025. Numerical example: REEEM assumptions. As of 12 October 2026.

Mario Willatowski | REEEM Consulting & Partner

mwillatowski@reeem-consulting.com

+49 30 39728968

reeem-consulting.com

Digital REEEM contact card | Save contact



QR / vCard